Betex 明达漆业(星)私人有限公司
Brightex Paints (Singapore) Pte. Ltd.
53 Tuas Avenue 1, Singapore 639502
TEL: 6863 5411   FAX: 6863 5411
EMAIL: enquiry53@brightexpaints.com

(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Woodtex

Description	A pigmented gel wood stain for interior wood surfaces
Recommended Use	Seal and stain the wood
Characteristics	- Easy apply - Seal and beautify the wood grain - Easy to handle
Colour	Refer to Woodtex Colour chart
Technical Data	Specific Gravity (25ºC) : 1.00 ± 0.05 Flash Point : 40ºC
Application Data	Application Method : Wiping Thinner : 0 - 5 % by weight Thinning Ratio : Turpentine Theoretical Coverage : Approx. 15 - 20 m²/L
Directions of Use	Ensure surface is smooth, clean and dry. Sand to ensure a smooth surface and remove any previous coating or treatment (e.g. wax or grease). Remove all dust from sanding. Rub Woodtex on the wood using a clean, lint-free cloth with a circular motion. Wipe away the excess in the direction of the wood grain.
Storage	Should be tightly sealed and stored in cool, dry place. Keep away from open flames.
Packaging	1 L
Handling and Safety	As it contains solvent, the product requires special care in handling. Avoid any eye and skin contact. For further information please refer to SDS.
Disclaimer	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept

Woodtex

any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.