

(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Betex Gloss Finish No. 31

Document No.: TDS-SB0011Rev01 Revised Date: 1/Nov/2016

Description	A thermoplastic acrylic based lacquer	
Recommended Use	A finishing coat for wood and metal substrates	
Finish	Gloss	
Colour	Clear	
Characteristics	Fast Drying	
	Non-yellowing	
	Good weather resistar	nce
Technical Data	Specific Gravity (25°C)	: 0.94 ± 0.10
	Flash Point	: 25°C
Application Data	Application Method	: Spray
	Thinner	: Brightex Auto Lacquer Thinner AAA
	Thinning Ratio	: 0 - 20 % by volume
	Theoretical Coverage	: Approx. 8 m²/L
	Dry Film Thickness	: Approx. 20 microns
	Drying Time	: Touch Dry : Approx. 10 – 15 minutes
		Hard Dry : Approx. 1 h
D: (' (II		
Directions of Use	Ensure surface is smooth, clean and dry. Sand to ensure a smooth surface and remove any previous coating or treatment (e.g. wax or grease). Remove all dust from sanding. Apply 1 coat of Betex Etching Primer Touch-up with Betex Patina Finish for Special effects. Apply 1 -2 coat of Betex Gloss Finish No. 31.	
Storage	Should be tightly sealed and stored in cool, dry place. Keep away from open flames.	
Daakaaina	41 51	
Packaging	1L, 5L	
Handling and Safety	As it contains solvent, the product requires special care in handling. Avoid any eye and skin contact.	
rialianing and ballety		
	For further information please refer to SDS.	



(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR

Betex Gloss Finish No. 31

Document No.: TDS-SB0011Rev01 Revised Date: 1/Nov/2016

Disclaimer

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.