BETEX
明达漆业（星）私人有限公司
Brightex Paints (Singapore) Pte. Ltd.
53 Tuas Avenue 1, Singapore 639502
TEL: 6863 5411   FAX: 6863 5411
EMAIL: enquiry53@brightexpaints.com

(Paints Manufacturer & Chemical Industrial Supplier)

TECHNICAL DATA SHEET FOR
Easy Bleach 202

Description	Easy Bleach 202 is a wood bleach use to lighten the natural colour from the wood. It is intended for professional use only.
Recommended Use	Lighten the natural colour of natural wood
Application Areas	Natural Wood
Characteristics	• Effective • Controllable • Ready-to-Use • Easy to apply
Appearance	Clear Odourless Liquid

Technical Data	Specific Gravity (25ºC)	:	1.07 ± 0.03
Application Data	Application Method	:	Brush, Roll
	Dilution	:	Ready for Use or dilute with water
	Coverage	:	Approx. 12 m²/L

Directions of Use	1) Sand the wood with sand paper to make a surface smooth. 2) Remove any wood dust generated during sanding. 3) Brush Easy Bleach 202 on the surface. 4) Let it dry for more than 24 hours. 5) Sand the dried surface with sand paper and remove all the wood dust. 6) Apply any Brightex Products on the treated surface.
Storage	Should be tightly sealed and stored in cool, dry place.
Packaging	500ml
Handling and Safety	The product requires special care in handling. Avoid any eye and skin contact. For further information please refer to SDS.
Disclaimer	The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he/ she wishes to use it. As we have no control over the treatment of the product, the surface preparation, application or other factors affecting the use of the

product, we are not responsible for its performance, nor would we accept any liability whatsoever or howsoever arising from the use of the product. The information contained in this data sheet may be modified by us from time to time, and without notice, in light of our experience and product development.